













Typar.

DuPont™ Typar® SF95

DECLARATION OF PERFORMANCE - DoP-Typar® SF95-02

1. Unique identification code of the product-type: **DuPont™ Typar®**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): **SF95**
3. Intended Uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Filtration, Filtration + Separation and Protection**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5): **DuPont de Nemours (Luxembourg) S.à.r.l., Rue General Patton, L-2984 Luxembourg**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): -
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 2+**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard, **the notified body KIWA TBU GmbH, No. 0799, performed initial inspection of the manufacturing plant and of factory production and continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued the certificate of conformity of the factory production control.**
8. In case of European Technical Assessment: -
9. Declared performance:

Harmonised Technical Specifications

				
N 13249 : 2016	EN 13250 : 2016	EN 13251 : 2016	EN 13252 : 2016	EN 13253 : 2016
				
EN 13254 : 2016	EN 13255 : 2016	EN 13256 : 2016	EN 13257 : 2016	EN 13265 : 2016

Essential characteristics	Test Method	Unit	Performance
Tensile Strength T_{max}	EN ISO 10319	kN/m kN/m	MD 25.0 (- 3.3) CMD 25.0 (- 3.3)
Elongation ϵ_{max}	EN ISO 10319	% %	MD 50 (+/- 11.5) CMD 45 (+/- 10.3)
Protection efficiency strain at 300 kPa	EN 13719	%	1.2 (+ 0.9)
Pyramid puncture resistance	EN 14574	N	275 (- 50)
Dynamic Perforation Resistance D_c	EN ISO 13433	mm	17 (+ 3.4)
Resistance to Static Puncture F_p	EN ISO 12236	kN	3.500 (- 0.35)
Opening Size O_{90}	EN ISO 12956	μm	70 (+/- 21)
Water Permeability V_{H50}	EN ISO 11058	m/s	$5 \cdot 10^{-3}$ (- $1.5 \cdot 10^{-3}$)
Durability in accordance with Annex B	To be covered within 2 weeks after installation. Predicted to be durable for 100 years in natural soils with $4 \leq \text{pH} \leq 9$ and soil temperatures $\leq 25^\circ\text{C}$ on the basis of the results of test method B.4.2.2 (112 days) of Annex B.		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Paul Meyers

Luxembourg: 01/01/2018

Managing Director and Works Director - DuPont de Nemours (Luxembourg) S.à r.l.